




# SELF-CONTAINED EMERGENCY LIGHT SERIES: MP12-5



## SPECIFICATIONS

- INPUT VOLTAGE : 220 V AC/50Hz +/-10%
- TYPE OF BATTERY : SEALED LEAD ACID
- LAMP USED : SEALED DICHROIC TUNGSTEN HALOGEN
- MODE OF OPERATION : NON MAINTAINED
- OPERATING TEMPERATURE : Ta 40 C
- CHARGER : CONSTANT VOLTAGE & CURRENT LIMIT
- CHARGER CURRENT : LIMITS CURRENT TO 100% OF FULL LOAD  
CURRENT DOWN TO SHORT CIRCUIT CONDITION
- PROTECTION : AC.FUSE / DC.FUSE / LOW VOLTAGE CUT OFF TO  
PREVENT BATTERY OVER DISCHARGE
- CONSTRUCTION : ELECTRO GALVANISED STEEL CASE EPOXY POWER COATED
- COMPLIANCE : IEC. 598-2-22

MODEL	BATTERY SEALED LEAD ACID	LAMP HEAD	LAMP WATT	DURATION	WEIGHT
MP12-5CS 10-2	12V - 5Ah	SQUARE	2 x 10 W.	2 HR.	4 KG.
MP12-5CS 20-2	12V - 5Ah	SQUARE	2 x 20 W.	1 HR.	4 KG.